# MULTIPURPOSE CART

Carts designed specifically for remote service and built to last.



LTI's molded fiberglass & stainless steel food bar is durable & incredibly easy to clean, looking new for 20 years – outlasting any plastic or laminated unit.





# **Multipurpose Cart**

MODEL NUMBER MPC-74

- 74-3/8" long x 30" wide x 34" high
- Molded Fiberglass

#### **STANDARD MODEL:**

- Two Separate Insulated Wells Accommodate 3-Pan and 2-Pan
- Single-Sided Service with Retractable Buffet Shield
- Single-Tier Sloped Overshelf (14-gauge Stainless Steel)
- Stainless Steel Push Handle
- Available in Black, White, Regal Blue, and Candy Apple Red
- 5" Casters with Brakes on All Wheels

#### **OPTIONAL EXTRAS:**

- · End Drop Shelf
- · Vinyl Graphics on 4 Sides
- Decals (each) Art Print-Ready Files Provided Max size of 24" x 48" (if not, design fee will be applied)
- · Sign Post with Sign and Menu Board



SHOWN WITH OPTIONAL EXTRAS End Drop Shelf, Vinyl Graphics, Sign Post with Sign & Menu Board

## Vinyl Graphic Wrap Options - choose one of these designs for the cart



Vinyl Graphics 1



Vinyl Graphics 6



Vinyl Graphics 2



Vinyl Graphics 7



Vinyl Graphics 3



Vinyl Graphics 8



Vinyl Graphics 4



Vinyl Graphics 9



Vinyl Graphics 5



Vinyl Graphics 10



# **MULTIPURPOSE CART**

### **SPECIFICATION**

Top to be 30" wide and fabricated from 14-gauge **stainless steel** with square turndown on all sides and corners fully welded, ground and polished. To have #4 satin finish with all edges having #7 hi-lite finish.

Body to be **seamless molded fiberglass** (F.R.P.) with smooth exterior surfaces and rounded corners. To be constructed by a hand lay-up process with four layers of 1.5 oz continuous strand fiberglass mat, plus a 24 oz layer of woven roving on the bottom for added strength. To be flame retardant per specification ASTM E-162 having a flame spread of 25 or less. Body interior to be reinforced at each end with 4" wide, 12-gauge galvanized steel channelwelded to form integral "U" frame for maximum stress relief. The ice cooled cold pan shall be of 18-gauge stainless steel and be 6" deep. The welded watertight pan to be double wall construction fully insulated urethane insulation with sectional,

removable false bottom. A full perimeter plastic laminate breaker strip shall separate the top from the cold pan.

The cold pan to have 1" open brass drain with extension to shutoff valve below base.

5" diameter x 2" wide, ball bearing, swivel type casters to be non-marking and with brakes on all wheels. Casters to be mounted with internal and external bracing for maximum stress relief.

Standard cart will have Single-Sided Service with retractable buffetshield and Single-Tier sloped overshelf 14-gauge **stainless steel**.

The tray slides shall be 16-gauge **stainless steel**, 8" wide with edges turned down square and all corners fully welded, ground and polished. Support brackets to be adjustable 14-gauge **stainless steel** fold down type. Bracket to have the ability to be adjusted for ¼" in height and leveling.

