

Solid Top 90° Wedge Filler Unit

Molded Fiberglass (MF)

Project: _			
•			
ltem:			

Quantity:

Date:

Models

☐ CP-STW-MF-90

Standard Features

- √ 14 gauge stainless steel top
- ✓ Molded fiberglass body
- √ 5" Locking Swivel Casters

CP-STW-MF-90 shown with option: (SS) Stainless Steel Legs







U.L. Sanitation Classified to NSF Standards

_					
	ubaraae	directiona	i tiow in	servina	lines

- Makes a perfect 90° turn in any serving line
- Sanitary, easy to clean design

Specifications

Top - Top to be 30" wide and fabricated from a minimum of 14 gauge stainless steel with square turndown on all sides and corners fully welded, ground and polished. Top to have #4 satin finish.

Body (MF) - Body to be seamless molded fiberglass (F.R.P.) with smooth exterior surfaces and rounded corners. To be constructed by a hand lay-up process with four layers of 1.5 oz continuous strand fiberglass mat, plus a 24 oz layer of woven roving on the bottom for added strength. Fiberglass to be flame retardant per specification ASTM E-162 having a flame spread of 25% or less. Body interior to be reinforced at each end with 4 wide, 12 gauge galvanized channels welded to form integral U frame for maximum stress relief.

Options

Top Options

- ☐ Height Other Than Standard 36" (Specify _____)
- ☐ (MR) #7 Hi-Lite Edge

Tray Slide/Cutting Board Options

- ☐ (A) Beaded, Stainless Steel Tray Slide
- ☐ (B) Flat Surface, Stainless Steel Tray Slide
- ☐ (C) Tubular Stainless Steel Tray Slide

Base Options

- ☐ (MM) Vertical Trim Strips
- ☐ (SS) Stainless Steel Legs
- ☐ (TK) S/S Toe Kick


Electrical Options


☐ (DD) Convenience Outlet, Flush

REV 9/4/24



Approvals:





END VIEW

Model	LxWxH	Approx. Ship Weight
CP-STW-MF-90	30" x 30" x 36"	225 lbs.

Décor Options (Contact Factory)

- ☐ Vinyl Graphic
- ☐ Stand Off Panel

(Specify Materials

We reserve the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacement for previously purchased equipment.

All equipment to be built in accordance with the Underwriters Laboratories. Inc. and the National Sanitation Foundation, Inc. standards and shall bear the Underwriters Laboratories, Inc. listing label for safety and the Underwriters Laboratories classification label for sanitation.

REV 9/4/24